








Hybrid Relief Valves

	<i>Cartridge Type</i>	<i>Page</i>
	Direct Acting Relief Valve - Before Check	156
	Direct Acting Relief Valve - After Check	157
	Ventable, Pilot Operated, Balanced Piston, Relief Valve - Before Check	158
	Ventable, Pilot Operated, Balanced Piston, Relief Valve - Before Check with Integral Pilot Control Cavity	159





DIRECT ACTING RELIEF VALVE - BEFORE CHECK



Capacity	Typical Cartridge Model Code	Cavity	Cartridge Dimensions					Installation Torque (Nm)
			a	b	c			
					L	C	K	
40 L/min.	HRDA - LAN	T - 11A	35,0	22,2	78,9	80,2	85,0	45/50

Performance Curves

HRDA



- Maximum operating pressure = 350 bar
- Maximum valve leakage at reseal = 0,3 cc/min.
- Reseat exceeds 85% of crack pressure
- Factory pressure setting established at 15 L/min.
- Free flow check cracking pressure = 1,7 bar
- Typical response = 2 ms
- The check portion of the valve has a maximum leakage rate of less than 0,07 cc/min.
- Note: This valve deviates from Sun's normal flow path for three port relief valves; port 2 is the inlet, port 1 is the system and port 3 is tank. Therefore, it is probably not useable in existing standard Sun relief manifolds.

HRDA - LAN



Nominal Capacity	Control**	Adjustment Range	Seal
D 40 L/min.	L Standard Screw Adjustment	A 35 - 210 bar	N Buna-N
	C Tamper Resistant Factory Set	W 55 - 315 bar	V Viton
	K Handknob		

** See page 162 for information on Control Options

Customer may specify pressure setting.

Visit www.sunhydraulics.com for detailed and complete technical information on our full line of products.


DIRECT ACTING RELIEF VALVE - AFTER CHECK



Capacity	Typical Cartridge Model Code	Cavity	Cartridge Dimensions					Installation Torque (Nm)
			a	b	c			
					L	C	K	
40 L/min.	HRDB - LAN	T - 11A	35,0	22,2	78,9	80,2	85,0	45/50

Performance Curves

HRDB



- Maximum operating pressure = 350 bar
- Maximum valve leakage at reseal = 0,3 cc/min.
- Reseat exceeds 85% of crack pressure
- Factory pressure setting established at 15 L/min.
- Free flow check cracking pressure = 1,7 bar
- Typical response = 2 ms
- The check portion of the valve has a maximum leakage rate of less than 0,07 cc/min.
- Note: This valve deviates from Sun's normal flow path for three port relief valves; port 2 is the inlet, port 1 is the system and port 3 is tank. Therefore, it is probably not useable in existing standard Sun relief manifolds.

HRDB - LAN



Nominal Capacity	Control**	Adjustment Range	Seal
D 40 L/min.	L Standard Screw Adjustment	A 35 - 210 bar	N Buna-N
	C Tamper Resistant Factory Set	W 55 - 315 bar	V Viton
	K Handknob		

** See page 162 for information on Control Options

Customer may specify pressure setting.

Visit www.sunhydraulics.com for detailed and complete technical information on our full line of products.



VENTABLE, PILOT OPERATED, BALANCED PISTON, RELIEF VALVE - BEFORE CHECK



Capacity	Typical Cartridge Model Code	Cavity	Cartridge Dimensions					Installation Torque (Nm)
			a	b	L	C	K	
40 L/min.	HVCA - LAN	T - 21A	35,0	22,2	78,9	80,2	85,0	45/50

Performance Curves

HVCA



- Maximum operating pressure = 350 bar
- Maximum valve leakage (port 2 to port 3) = 32,8 cc/min. at 70 bar
- Factory pressure setting established at 15 L/min.
- Free flow check cracking pressure = 1,7 bar
- Typical response = 10 ms
- Minimum setting is 5 bar for all spring ranges.
- Back pressure at port 3 (tank) is directly additive to the valve setting at a 1:1 ratio.
- Pressure at port 4 (vent) controls the valve below its setting.
- The check portion of the valve has a maximum leakage rate of less than 0,07 cc/min.
- Note: This valve deviates from Sun's normal flow path for four port relief valves; port 2 is the inlet, port 1 is the system, port 3 is tank and port 4 is vent. Therefore, it is probably not useable in existing standard Sun relief manifolds.

HVCA - LAN



Nominal Capacity	Control**	Adjustment Range	Seal
C 40 L/min.	L Standard Screw Adjustment	A 5 - 210 bar	N Buna-N
	C Tamper Resistant Factory Set	B 5 - 105 bar	V Viton
	K Handknob	D 5 - 55 bar	
		W 5 - 315 bar	

** See page 162 for information on Control Options

Customer may specify pressure setting.

Visit www.sunhydraulics.com for detailed and complete technical information on our full line of products.

VENTABLE, PILOT OPERATED, BALANCED PISTON, RELIEF VALVE - BEFORE CHECK WITH INTEGRAL PILOT CONTROL CAVITY




The -8 control option allows the pilot control valve to be incorporated directly into the end of the relief cartridge via the T-8A cavity. These pilot control cartridges are sold separately and include electro-proportional, solenoid, air pilot, and hydraulic pilot operation. See Pilot Control Cartridges on page 121.

Capacity	Typical Cartridge Model Code	Cavity	Cartridge Dimensions			Installation Torque (Nm)
			a	b	c	
40 L/min.	HVCA - 8DN	T - 21A	35,0	22,2	45,2	45/50


Performance Curves

HVCA-8



- Maximum operating pressure = 350 bar
- Maximum valve leakage (port 2 to port 3) = 32,8 cc/min. at 70 bar
- Free flow check cracking pressure = 1,7 bar
- Minimum setting is 5 bar for all spring ranges.
- Back pressure at port 4 (tank) is directly additive to the valve setting at a 1:1 ratio.
- The check portion of the valve has a maximum leakage rate of less than 0,07 cc/min.
- Note: This valve deviates from Sun's normal flow path for four port relief valves; port 2 is the inlet, port 1 is the system, port 3 is tank and port 4 is vent. Therefore, it is probably not useable in existing standard Sun relief manifolds.
- With the -8 control option, the main stage valve should first be installed to the correct torque value. The T-8A pilot control valve should then be installed into the main stage valve to its required torque value.

HVCA - 8DN



Visit www.sunhydraulics.com for detailed and complete technical information on our full line of products.

NOTES